

Safety Exhaust Couplers

Couplers & Plugs

MILTON® Safety Exhaust Couplers are designed to disconnect air connections is a safe manner. With disconnection utilizing a protective sleeve and a controlled release of air, users can quickly change out tools without the risk of hose whip that can cause injuries to the operator and damages to surrounding tools and products



3/8" Basic Flow

H-P STYLES





1/2" Basic Flow G G
(.125) (.375)
STYLES

Scan here for product demo



Locking Safety Sleeve

Connects to Multiple Interchanges

NPT connections



Safety Exhaust Couplers

Couplers & Plugs



Product Overview

- Push-type connection
- Safety sleeve
- Rugged steel body
- Protective bumpers on larger sizes
- Universal style offering
- National pipe thread fitting end
- 200 PSI maximum operating pressure
- 225°F maximum operating temperature

Features

- Convenient and time-saving
- Disengaging fitting without dangerous blow back
- · Strength and durability
- Product preservation
- Can be used with multiple style plugs
- Easy to install
- Provides greater power
- Work environment flexibility







BOXED (5 QTY)	BULK (50 QTY)	RETAIL PKG	EA	FLOW SIZE	NPT	CONNECTION	STYLE INTERCHANGE	BUMPERS
1750	1750BK	s-1750	1	1/4"	1/4"	Female	M [®] -A-T-V-L	N
1751	1751BK	s-1751	1	1/4"	1/4"	Male	M®-A-T-V-L	N
1752	1752BK	s-1752	1	1/4"	3/8"	Female	M [®] -A-T-V-L	N
1753	1753BK	s-1753	1	1/4"	3/8"	Male	M®-A-T-V-L	N
1754	1754BK			1/4"		1/4" ID Hose Barb	M [®] -A-T-V-L	N
1755	1755BK			1/4"		3/8" ID Hose Barb	M®-A-T-V-L	N



BOXED (5 QTY)	BULK (50 QTY)	RETAIL PKG	EA	FLOW SIZE	NPT	CONNECTION	STYLE INTERCHANGE	BUMPERS
1756	1756BK	s-1756	1	3/8"	1/4"	Female	H-P	Υ
1757	1757BK	s-1757	1	3/8"	1/4"	Male	H-P	Υ
1758	1758BK	s-1758	1	3/8"	3/8"	Female	H-P	Υ
1759	1759BK	s-1759	1	3/8"	3/8"	Male	H-P	Υ
1773	1773BK	s-1773	1	1/2"	1/2"	Female	G-G	Y
1774	1774BK	s-1774	1	1/2"	1/2"	Male	G-G	Υ