

Sump Alarm

SUMP ALARM 12VAC HIGH WATER ALARMS



This indoor / outdoor water alarm is made from rugged industrial materials which can sustain outdoor elements. Perfect for Septic Alarms and Outdoor High Water Alarm.

Product Features

- 1 Rated for indoor and outdoor use
- 2 5 year warranty from time of sale
- 3 Indicates high level visually and audibly
- 4 1" Red Alarm LED with Pulsing Horn, 90dB at 10cm
- 5 Optional sound muffling boot
- 6 Thermoplastic ABS enclosure conforms to UL94/HB
- 7 Enclosure rated to NEMA 4X / IP67
- 8 Has (4) rear mounting holes and mounting feet for customer mounting
- 9 Prewired with float switch, counterweight and power cord
- 10 Includes wall anchors and hardware, wire ties and installation instructions
- 11 Mercury Free Float Switch rated for 10,000,000 operations
- 12 Float Switch Connects Via Internal Screw Terminals
- 13 6' AC power cord, NEMA 5-15P
- 14 Suitable for use with potable water, septic systems and low density oils
- 15 [See installation details at http://bit.ly/levelalarm](http://bit.ly/levelalarm)
- 16 Sump Alarm™ is ready to operate out of the box
- 17 Alarms can detect High Level or Low Level (not both)
- 18 Extremely low power (≈15 milliAmperes @120AC)
- 19 Hardened Electronics withstand -40°F to + 140°F, up to 99% Humidity



PART NUMBER*	SUPPLY VOLTAGE		FLOAT CORD LENGTH		PLUG	SHIPPING WEIGHT
	VAC		FEET	METERS		
SA-120VAC-1L-10F-WIFI	120		10	3	2359	2.4
SA-120VAC-1L-16F-WIFI	120		16	5	2359	2.5
SA-120VAC-1L-16SB-WIFI	120		16	5	2368	3.8
SA-120VAC-1L-20SB-WIFI	120		20	6	2368	4
SA-120VAC-1L-10C-WIFI	120		10	3	Conductivity	2.2
SA-120VAC-1L-16C-WIFI	120		16	5	Conductivity	2.3
SA-120VAC-2L-33F-WIFI	120		33	10	2359	3.5
SA-120VAC-2L-16SB-WIFI	120		16	5	2368	5.2
SA-120VAC-2L-33SB-WIFI	120		33	10	2368	5.8
SA-120VAC-2L-16C-WIFI	120		16	5	Conductivity	2.4

Sump Alarm

PART NUMBER CONFIGURATION



SA-120VAC-{x}L-{sensor length}{sensor type}-WIFI

SA = SumpAlarm

{x} = Indication

0 = Red Light Only (No Horn)

1 = Red Light & Horn

2 = 1 + White LED Power Light

WIFI Capable

{type} = Sensing Method

_ or F = 2359 Float Switch (Standard)

SB = SludgeBoss Heavy Duty Float (Sewage)

C = Conductivity Probes (Clear Water)

{sensor length} = Cord Length

10 (F,C)

16 (F,C,SB)

20 (SB)

33 (F,C,SB)

100 (F,C,SB)

Common Examples

SA-120VAC-10F-WIFI

SA-120VAC-20SB-WIFI

SA-120VAC-10C-WIFI



2368 SludgeBoss Float Switch



Conductivity Probes



2359 Waterboss Float Switch


HIGH WATER ALARMS

Wireless & Notification Features


- 1 Dedicated 2.4Ghz Wi-Fi Device, FCC Approved, 802.11 b/g/n
- 2 Compatible with WPAPSK, WPA2PSK, OPENWEP, SHAREDWEP Security
- 3 Patented "Health Pulse" System Alerts User if Device Stops Reporting or Power is Lost
- 4 Delivers Notifications to Up To Five Email Addresses, Five Text Locations, and Five Voice Numbers
- 5 E-Mail Notifications are Free for Life, Unlimited Voice and Text are \$0.99 per month
- 6 Text Message Notifications are Sent with PURE SMS Technology
- 7 Users Create an Account and Register the Unit through the Website at www.SumpAlarm.Com
- 8 [More information available at YouTube.Com/c/SumpAlarmInc](https://www.youtube.com/c/SumpAlarmInc)
- 9 Hardened Electronics withstand -40°F to + 140°F, up to 99% Humidity

INCLUDED ACCESSORIES


SENSOR



CABLE WEIGHT (2359)



MOUNTING FEET



WALL ANCHORS

