BEFORE USE: Shake vigorously before using. The use of boiling water, bleach, anti bacterial soap or other chemicals will negatively impact performance.

DOSAGE: • Pour 1 oz. per 40 gallons of tank capacity into toilet and flush. First time use or after prolonged lay up: Double the above amounts. Dose after holding tank is pumped out. Double the dose in temperatures over 85 degrees. Dosage based on 2 persons with average use. Individual use may vary.

DIRECTIONS: For black water tanks.pour 1 oz per 40 gallons of tank capacity into toilet, (black water) fill toilet and flush. For gray water tanks, pour 1 oz. per 40 gallons of tank capacity into drain (gray water) and run plenty of water.

ELIMINATE ODORS • LIQUIFY SOLIDS • FASTER PUMP OUTS

INGREDIENTS: WATER, BIO-SURFACTANTS, ENZYME PRODUCING BACTERIA, ODOR COUNTERACT, CITRUS SCENT NON-STAINING RED DYE.



EcoStrong's Holding Tank Treatment Liquid is a fast acting, concentrated, biologic solution for your RV's holding tank. Packed with over 50 billion specialized, enzyme-producing bacteria, EcoStrong's Holding Tank Treatment Liquid has unmatched waste liquification, odor eliminator and sensor cleaning technology. EcoStrong's Holding Tank Treatment Liquid works faster than powders and disperses more evenly throughout the tank.

EcoStrong's Holding Tank Treatment Liquid uses six strains of bacteria to break down human waste, F.O.Gs, sugars, toilet paper and hair. This treatment does not contain any added harmful enzymes that destroy seals and gaskets in your tank.

Suitable for both aray and black water tanks.

STORAGE: DO NOT FREEZE

SUPPORT: 800-667-0517 1180 Atlantic Drive, West Chicago, IL 60185



THE GOLD STANDARD IN RV TANK TREATMENTS

WARNING: KEEP OUT OF REACH OF CHILDREN. Do not inaest. Wash hands thoroughly after each use. Keep out of eyes and/or open sores. May cause eye irritation. If irritation occurs rinse eyes thoroughly with water for several minutes. If irritation persists, seek medical attention.





