


# 30 TRAY / 53 SQ. FT COMMERCIAL-GRADE DEHYDRATOR

COMMERCIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL



Uniform Drying  
Without  
Rotation



Completion  
Cooling Cycle



Time and  
Temp Memory  
Function



99 Hour  
Timer



30-90°  
Precision  
Thermostats



Glass  
Observation  
Window



Ambient  
Air Mode



Food-Grade  
304 Stainless  
Steel

## 30CUDG SPECIFICATIONS

Max Power Usage	3 kW (1 kW x 3 Zones)	Total Tray Area	53 sq. ft
Avg Power Usage	1.2 kW (400 W x 3 Zones)	Total Trays	30
Voltage / Frequency	200-240V/50-60Hz	Tray Dimensions	16" x 16"
Max Amperage	12A	Space Between Trays	1 2/5"
Safety Breaker Required	Single Phase/15A	Tray Mesh Spacing	5/16" x 5/16"
Temperature Range	Ambient Mode, 85 - 195°F	Machine Weight	96 lbs
Timer	0 - 99hr	Product Dimensions (W x H x D)	17.25" x 4' 6.5" x 21.25"
Independent Zones	3	Features	Memory Function, Ambient Air Mode
Product Material	Food grade 304 stainless steel trays; Commercial grade stainless steel housing & latches; Aluminum door handle; Tempered glass observation window; Control Panel with PVC finish.		