


60 TRAY / 107 SQ. FT COMMERCIAL-GRADE DEHYDRATOR

COMMERCIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL



Uniform Drying
Without
Rotation



Completion
Cooling Cycle



Time and
Temp Memory
Function



99 Hour
Timer



30-90°
Precision
Thermostats



Glass
Observation
Window



Ambient
Air Mode



Food-Grade
304 Stainless
Steel

60CUDG SPECIFICATIONS

Max Power Usage	4.5 kW (1.5 kW x 3 Zones)	Total Tray Area	107 sq. ft
Avg Power Usage	1.8 kW (600 W x 3 Zones)	Total Trays	60
Voltage / Frequency	200-240V/50-60Hz	Tray Dimensions	16" x 16"
Max Amperage	19.56A	Space Between Trays	1 2/5"
Safety Breaker Required	Single Phase/25A	Tray Mesh Spacing	5/16" x 5/16"
Temperature Range	Ambient Mode, 85 - 195°F	Machine Weight	190 lbs
Timer	0 - 99hr	Product Dimensions (W x H x D)	4' 7.5" x 3' .5" x 22"
Independent Zones	3	Features	Memory Function, Ambient Air Mode
Product Material	Food grade 304 stainless steel trays; Commercial grade stainless steel housing & latches; Aluminum door handle; Tempered glass observation window; Control Panel with PVC finish.		