



TITEBOND QUICK & THICK MULTI-SURFACE GLUE

Titebond Quick & Thick Multi-Surface Glue is the thickest, fastest-drying water-based glue available for use with porous and semi-porous materials. It is ideal for wood, pottery, ceramic, stone, glass, fabrics, leather and most craft-type materials. Titebond Quick & Thick Multi-Surface Glue provides a strong initial tack and fast speed of set, yet allows realignment of working pieces. It also develops a bond stronger than the wood itself, dries clear and is unaffected by finishes.



Features & Benefits

- 2X Faster – 3X Thicker than traditional PVA glues
- Dries clear – Paintable
- Ideal for the woodshop, home and craft projects
- Fill small cracks and gaps
- Unaffected by finishes
- Excellent sandability on wood
- Designed for interior projects
- Water cleanup & non-toxic
- Nonflammable — No offensive odor

Conforms to ASTM D4236

Application Guidelines

Application Temperature: Above 50°F (10°C)

Open Assembly Time: 3-5 minutes (70°F./50%RH)

Total Assembly Time: 10-15 minutes (70°F./50%RH)

Minimum Required Spread : Approximately 6 mils or 250 square feet per gallon

Required Clamping Pressure: Enough to bring joints tightly together (generally, 100-150 psi for soft woods, 125-175 psi for medium woods and 175-250 psi for hardwoods)

Method of Application: Plastic bottles for fine applications; glue may also be spread with a roller, spreader or brush.

Cleanup: Damp cloth while glue is wet. Scrape off and sand dried excess.

Physical Properties

Type: Thixotropic polyvinyl acetate

Calculated VOC: 2.4 g/L

State: High-viscosity liquid

Weight Per Gallon: 9.0 lbs.

Color: White

Dried Film: Clear

Flashpoint: > 200°F

Solids: 60%

Freeze / Thaw Stability: Stable up to 2 cycles

Viscosity: 36,500 cps

pH : 4.8

Chalk Temperature: To assure a good bond, 50°F is the lowest recommended temperature of the glue, air and materials during application.

Storage Life: 24 months in tightly closed containers at 75°F

Limitations

Titebond Quick & Thick Multi-Surface Glue is not recommended for exterior use or where moisture is likely. For exterior applications, use Titebond III Ultimate Wood Glue or Titebond II Premium Wood Glue. Not for structural or load bearing applications. Not recommended

for photos, washable wearables, metals, plastics or rubber. Do not use when temperature, glue or materials are below 50°F. Freezing may not affect the function of the product but may cause it to thicken. Agitation should restore product to original form. Read SDS before use. For wood, sand glued area thoroughly before staining. Store at room temperature. **KEEP FROM FREEZING. KEEP OUT OF THE REACH OF CHILDREN.**

Product SKUs

Part Number	UPC	Case UPC	Size	Weight	Units Per Package	Packages Per Pallet
2403	037083024036	10037083024033	8 Oz. Bottle	7.26	12	160
2404	037083024043	10037083024040	16 Oz. Bottle	15.14	12	100

Important Notice: Our recommendations, if any, for the use of this product are based on tests believed to be reliable. Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied, is made as to such use or effects incidental to such use, handling or possession or the results to be obtained, whether in accordance with the directions or claimed so to be. The manufacturer expressly disclaims responsibility therefore. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use.

2020 Bruck Street, Columbus, Ohio 43207
CUSTOMER SERVICE 1-800-669-4583
TECH SERVICE 1-800-347-4583
www.titebond.com

Franklin International