
MAXIMUM MOBILITY



 60% larger diameter & 2X wider wheels designed for the jobsite

والمارية المرادي والملطاء المتعاون والمتعادلة والمتعاون والمتعادلة والمتعاون والمتعادلة والمتعادلة والمتعادلة

DURABILITY



- Up to 750 lb payload
- 2X greater wall thickness

المالات والمالات المعالمة المراد المالية المتعالمة المتعالمة المتعالمة المتعالمة المتعالمة المتعالمة المتعالمة

• One-piece handle design

SECURITY



- Fully integrated 16-gauge steel panels enclosed by tongue & groove design
- Up to 70% reduction of assembly time



BEYOND MAXIMUM SECURITY™





DURABILITY

Built with a 50% higher load-rating than traditional carts used on jobsites.



SECURITY & ASSEMBLY

16-gauge steel panels with lockable steel doors to prevent theft. Easily put together in less than 10 minutes, saving up to 70% in assembly time. Reducing complexity with only one type of hardware required to assemble.







ARMOURED TRANSPORT

Flat top design for easier materials transport and work surface

Ergonomic handle to alleviate fatigue when pushing and pulling maximum payloads

2X wall thickness for jobsite durability and payloads



Electrical cord pass through with rubber grommet



Taller than
light-duty carts
for an elevated
work platform

Approx. Dimensions: 45.5" L x 27" W x 37" H



Don't need security? Meet the KT-01.

The KNAACK Transport provides the same mobility, durability, and easy assembly without the security armour.





PART NO.	DESCRIPTION	MATERIAL	SHIPPING DIMENSIONS H x W x D (in)	SHIPPING WEIGHT (lbs)	UPC
KAT-01	KNAACK Armoured Transport	Steel & HDPE	12 x 29 x 47.5	123	783965071871
KT-01	KNAACK Transport (no armour)	HDPE	9 x 29 x 47.5	75	783965072267

KAT-01 includes: Top tray, bottom tray, 4 legs, 2 fixed wheels, 2 swivel and locking wheels, armour panels, hardware **KT-01 includes:** Top tray, bottom tray, 4 legs, 2 fixed wheels, 2 swivel and locking wheels, hardware

800-456-7865 • KNAACK.COM