

U1P-Drive Full Synthetic Motor Oil

5W-30 API SP, ILSAC GF-6A

Auto – Light Truck | United States

Product Description

U1P-DRIVE SAE 5W-30 Full Synthetic Motor Oil, API SP, ILSAC GF-6A is a high performance full synthetic multigrade motor oil formulated for gasoline engines, combining 100% full synthetic base stocks with an Ultra-premium high performance additive package. This oil is designed for use in carbureted, fuel injected, turbocharged, and supercharged gasoline engines in both normal and extreme operating conditions.

U1P-DRIVE SAE 5W-30 Full Synthetic Motor Oil, API SP, ILSAC GF-6A exceeds the performance requirements of API SP, ILSAC GF-6A, and GM dexos1™ Gen 2 quality certifications. Delivers engine protection and cleanliness. Recommended for on-road and off-road use, light duty, and heavy duty. Creates a strong lubricant film in both cold and hot weather. Excellent for American, Asian, and European gasoline engines that require API SP quality motor oil and previous certifications. Substitutes older API (SN, SM, SL, SJ, SH, SG, SF, SE, SD, SC, SB, SA).

Features and Benefits

- Longer Engine life.
- Excellent overall lubrication and wear protection even at extreme driving conditions.
- Provides excellent cold start lubrication and reduces friction for better gas millage and control of emissions.
- Prevents the formation of varnishes, sludge and deposits that could be generated at high temperatures.
- Maximum protection against corrosion and rust formation.
- Reduces lubricant evaporation at high temperatures.
- Outstanding stable performance within the maximum oil change interval recommended by the vehicle's manufacturer.



Product Code

Presentation	SKU	Manufacture ID	UPC
1.05 QT / 1 Liter	UFS0530SPGF6AL	UL103	810050650243
1 US Gallon	UFS0530SPGF6AG	UL103	810050650236
1 JUG (5 QTS)	UFS0530SPGF6AJ	UL103	810050658287
5 Gallon Pail	UFS0530SPGF6AP	UL103	810050650229
55 Gallon Drum	UFS0530SPGF6AD	UL103	810050650212
265 Gallon Tote	UFS0530SPGF6AT	UL103	810050650205



This product meets or exceeds the requirements of:

API SP, API SN, API SM, API SL and API SJ	Honda
Chrysler MS6395	ILSAC GF-6A
Fiat 9.55535-CR1	Kia
Ford WSS-M2C 946-A / 946-B1 / 961-A1 / 946-A (5W-30)	Mazda
GM 6094 M / dexos1™ Gen 2 / dexos1™ Gen 3	Nissan
GWM	Subaru
HAVAL	Toyota



Properties and Specifications*

Parameter	Result
Appearance	Amber, liquid
Viscosity @ 40°C, cSt, ASTM D445	61.25
Viscosity @ 100°C, cSt, ASTM D445	10.8
Viscosity index, ASTM D2270	170
CCS Apparent Viscosity, cP, ASTM D5293	5,200@-35°C
MRV Apparent Viscosity, cP, ASTM D4684	18,000@-40°C
Pour point, °C, ASTM D97	-42
Flash point, °C, ASTM D92	215

*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.



Revised: 03/06/2023