

U1P-Drive Full Synthetic Multi-Vehicle Transmission Fluid

ATF DEXRON VI

Transmission | United States

Product Description

U1P-DRIVE Full Synthetic ATF Dexron® VI Multi-Vehicle is a premium synthetic automatic transmission fluid formulated with synthetic base stocks and ultra high-performance additives, for excellent performance and longer transmission life. Suitable for use in applications which require DEXRON® VI in a wide variety of American, Asian, and European cars with low viscosity ATF applications.

The new Dexron® VI standard exhibits more than twice the durability and stability in friction test compared with the previous Dexron® III standard fluid. Improved oxidation prevention, thermal stability, and friction modifiers to offer anti-wear capacity, heat stability and low temperature fluidity. Protects bearings, bushing and gears ensuring a consistent and smooth shift performance, even under extreme driving conditions. Approved to use in automatic transmissions and transaxles where Dexron® VI fluid is specified (Model Years 2006 and newer) and is backward compatible in older transmissions requiring Dexron® II or Dexron® III fluids.

Features and Benefits

- Enhanced friction coefficient and foam control additive promote smooth shifting and efficient torque transmission.
- Improved lubrication film strength, thermal stability, wear control and corrosion resistance to extend transmission life and improves fuel economy by reducing gear friction.
- Premium ATF that can be used for most new model automatic transmission cars.
- Increased resistance to oil oxidation and degradation minimizing the formation of lacquers, sludge, and other harmful deposits.
- Compatible with gaskets, rubber bands, plate seals and discs made with elastomers and other seal materials.
- Outstanding low temperature fluidity and improved protection of cooper and bronze components.



Product Code

Presentation	SKU	Manufacture ID	UPC
1.05 QT / 1 Liter	UFSDVIMVL	UL503	810050653541
1 US Gallon	UFSDVIMVG	UL503	810050653534
5 Gallon Pail	UFSDVIMVP	UL503	810050653527
55 Gallon Drum	UFSDVIMVD	UL503	810050653510
265 Gallon Tote	UFSDVIMVT	UL503	810050653503



This product meets or exceeds the requirements of:

GM	GM DEXRON® VI, III, IIIH, IIE, II
Ford	Ford MERCON®
JASO	JASO M315 1A-LV
Toyota	Toyota ATF WS
Mercedes Benz	MB 236.1, 236.2, 236.3, 236.5, 236.6, 236.7, 236.8, 236.9
Allison	Allison® C-3 & C-4
Audi	Audi 5 HP LT71141 (ZF 5HP 18FL/19FL/24A) Audi G 052-162-A1 A2 (ZF Lifeguard fluid 5, ZF No. S671 090 170)
Mitsubishi	Mitsubishi Diaqueen J2/3
Nissan	Nissan® Matic Fluid S
VW	VW G 055-025-A2 5 HP (ZF 5 HP 30)/(18FL,30)/19FL, 24A) TL 521 62
ZF	ZF, ZF TE-ML 09/09X/11A/11B
Mazda	ATF D-II, M-III, M-V, FZ, S-1, N-1, F-1, 3317
Honda	ATF-Z1 (Except CVT's) DW-1
Hyundai/Kia	SP-II, SP-IV, SP-IVM, Red 1
Subaru	ATF, ATF 5AT
BMW	BMX 7045E BMW JWS 3309 (T-IV) BMW LA 2634



Properties and Specifications*

Parameter	Result
Appearance	Red, Dyed Liquid
Viscosity @ 40°C, cSt, ASTM D445	29.5
Viscosity @ 100°C, cSt, ASTM D445	6.0
Viscosity index, ASTM D2270	155
Pour point, °C, ASTM D97	-52
Flash point, °C, ASTM D92	190
Brookfield Viscosity @-40°C, ASTM D2983, cP	12,000

*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Revised: 03/06/2023