





PRODUCT DATA SHEET

ACRYLIC ROOF COATING

DESCRIPTION

EZ On Coat* Acrylic Roof Coating is an acrylic elastomeric polymer fortified with fibers. It dries by evaporation to yield a non-yellowing, water-repellent surface. EZ On Coat* Acrylic Roof Coating is UV stable, and has exceptional abrasion resistance. A sustainable cool roof coating.

RECOMMENDED USES

EZ On Coat* Acrylic Roof Coating can be applied to surfaces such as metal, masonry, wood, and over EZ On Coat* primers after following preparation procedures.

APPLICATION

Surface to be treated must be clean. If necessary, remove all dust, grease and loose debris before applying this product.

Apply with a brush, roller, or sprayer at a rate of 1.00 gallon per 100 square feet per pass. Multiple passes may be applied at 1 gallon per 100 square feet.

BENEFITS

Mildew Resistant
Non-Toxic
Flexible
Easy Clean Up
Non-Yellowing
Abrasion Resistant
Energy Saving
Prevents Rust
Waterproof

TECHNICAL DATA

EMITTANCE: 90 ASTM C-1371

REFLECTANCE: .78%

FLEXIBILITY: Passed 180° Mandrel Bend Test

ASTM D-822

VISCOSITY: 6,000 – 9,000 cps

WEATHERABILITY: Passed 4000 Hours ATSM G-53

FIRE RESISTANCE: Class "A" in Assembly

FUNGAL RESISTANCE: Passed ASTM D-3273-73T

ELONGATION: 300% at 70° F ASTM 2370

CLEAN UP: Biodegradable citrus cleaning product

or soap and water

TENSILE: 380 psi ASTM D-1653A

PERMEABILITY: 1.8 perms ASTM D-1653A

SOLIDS BY WEIGHT: 60% +/- 2% ASTM D-1644

SOLIDS BY VOLUME: 52% +/- 2% ASTM D-2697

VOC: <50 grams per liter

WEIGHT: 11.67 lbs. per gallon +/- 5%

CAUTION: High humidity requires a longer time for water-based coatings to form a film that is rain resistant.

Avoid breathing fumes and prolonged contact with skin. Do not ingest. Keep containers
covered when not in use. When using, provide proper ventilation. Dispose of product
and container in accordance with local disposal codes.

CONSULT TECHNICAL DEPARTMENT FOR ANSWERS TO ANY QUESTIONS REGARDING USE OF THIS PRODUCT

System warranty available. When sold separate from system there is no warranty given, expressed or implied, through the values or statements made here, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by our in house and independent third party labs in order to obtain approval and/or classification. Acceptance, purchase and selection of these products are the sole responsibility of the buyer, buyer's agent, or the buyer's customer. EZ On Coat* assumes no responsibility for coverage, performance, or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER GUARANTY OR WARRANTY OF ANY KIND IS MADE BY EZ On Coat* OR ITS SUBSIDIARIES, EXPRESSED OR IMPLIED, STATUORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING COSMETIC APPEARANCE, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.