

EZ on Coat Premium Acrylic Primer Application Manual

DESCRIPTION

EZ on COAT® Acrylic Primer is a combination of high-grade latex acrylics in water. It dries by evaporation to a clear, high-luster surface that has exceptional abrasion resistance. This product does not alter the color of the surface being treated.

USES

EZ on COAT® Acrylic Primer can be used as a primer over metal, modifieds, smooth BUR, PVC, TPO, Hypalon, EPDM, etc. to increase adhesion.

APPLICATION

Surface should be clean, dry and sound. All existing surface dirt, oil, grease and debris should be removed before application. Apply with a brush, roller or sprayer. Do not dilute or alter this product. Apply at a rate of 0.5 - 1 gallon per 100 square feet. Apply at 50F and rising.

CLEAN UP

Biodegradable citrus cleaning products and soap with water.

WARRANTY

System warranty available. When sold separate from system there is no warranty given, expressed or implied, through the values or statements made here, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by our in house and independent third party labs in order to obtain approval and/or classification. Acceptance, purchase and selection of these products are the sole responsibility of the buyer, buyer's agent, or the buyer's customer. EZ on COAT® assumes no responsibility for coverage, performance, or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER GUARANTY OR WARRANTY OF ANY KIND IS MADE BY EZ on COAT® OR ITS SUBSIDIARIES, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING COSMETIC APPEARANCE, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

