

## Warranty Registration

To register your product for the warranty, visit our website at [123filter.com](http://123filter.com) and go to the "Warranty" tab.

We provide a 30-day money-back guarantee, a 1-year manufacturer warranty, and lifetime tech support for all of our products. However, we do not have order information from websites other than [123Filter.com](http://123Filter.com) (Amazon, Home Depot, etc.), so please fill in that information upon registering your system. If you have any questions or concerns about your product, please call or email us, or put it in the notes/comments upon registering your warranty. Your satisfaction is our business!

If you are happy with our products and service, please show your support by writing a product review on Amazon, even just a single line. It takes you just a minute but it means a lot to us. Thank you!



**iSpring** Water Systems

(678) 261-7611  
support@123filter.com  
www.123Filter.com



## iSpring AIG1 top mount installation kit user manual

Ver. 08/2021

### Product introduction

iSpring AIG1 top mount installation kit is tool-free and allows the installation of a standard drinking water faucet on the countertop without reaching under sink. It is designed to save time and hassle.

The product comprises two parts (Fig. 1 and 2):

- 1) a plate with a rubber side facing up and a metal side facing down, and
- 2) a threaded metal nut.



Fig. 1

Fig. 2

The product comprises two parts (Fig. 1 and 2):

- 1) a plate with a rubber side facing up and a metal side facing down, and
- 2) a threaded metal nut.

### Precautions

- 1) Before using this product, users must read and fully understand this manual to avoid any mishandling or injury.

2) This top mount installation kit is designed for 6/17" faucet stem and it fit 3/4" to 1-1/4" sink hole. You will need existing sink hole on the countertop to install this product.

3) This product contains small parts. Keep away from babies and small children or any individuals who have a tendency to place inedible objects in their mouths. Seek immediate medical attention if pieces are swallowed.

4) This product does not include faucet parts such as faucet stem.

### Installation procedures

To install, follow the steps described below:

1) Insert the plate with the rubber side up to the faucet stem. Install the metal nut onto the faucet stem, below the plate. It will keep the plate from falling (Fig. 3).

2) Lift and tilt the plate (Fig. 4).



Fig. 3



Fig. 4

3) Insert the faucet stem and the kit into the sink hole while keeping the plate in the tilted position. (Fig. 5).

4) Let go the plate. It will drop and latch on the metal nut via the triangular grooves located on both sides. Thereby, it will change from the tilted position to the horizontal position (Fig. 6).



Fig. 5



Fig. 6

5) Lift the faucet body to secure the plate and nut. While lifting, tighten the faucet by turning it clockwise (Fig. 7).

While lifting, tighten the faucet by turning it clockwise (Fig. 8).



Fig. 7



Fig. 8