



SC10

TURBO SEGMENTED RIM

800 Expert

HARD MATERIALS

Cat® 800 Expert Hard Material turbo segmented laser welded diamond blades are designed to cut incredibly fast & accurately. The turbo design extracts the fines & debris from the cut aggressively & make a neat cutting edge. High quality diamond grit & unique bonding matrix allows the blade to cut the hardest materials whilst having a great span of application across other substrates & materials. High quality engineered blank with cooling holes keeps the blade cool in the toughest conditions.

ATTRIBUTES

- FULLY HARDENED & HEAT TREATED STEEL CORE
- VENTED COOLING HOLES FOR RAPID HEAT DISPERSION
- 2X LASER WELDED FOR SAFETY & STABILITY OF SEGMENTS
- UNIQUE TURBO SEGMENT DESIGN FOR AGGRESSIVE CUTTING ACTION
- UNIQUE V TURBO DESIGN CLEARS ABRASIVE FINES FROM THE CUT & GENERATES LESS FRICTION
- UNIQUE BOND FORMULATION & HIGH QUALITY HIGH CONCENTRATION DIAMOND GRIT
- KEYHOLE GULLET DESIGN FOR DUST EXTRACTION FROM CUT
- VERY LONG LIFE & SPEED OF CUT.

APPLICATION

★★★★

HEAVILY STEEL REINFORCED CONCRETE, CRITICALLY HARD AGGREGATE CONCRETE (FLINT, CHERT), HARD TO MEDIUM AGGREGATE CONCRETE (CHERT - TRAP ROCK - RIVER GRAVEL), MEDIUM AGGREGATE CONCRETE (TRAPROCK - QUARTZ), SOFT - MEDIUM AGGREGATE CONCRETE (GRANITE - LIMESTONE), CLASS A ENGINEERING BRICK 125 N/MM², CLAY PIPE - ROOF TILES, CLAY PAVERS, QUARRY TILES, TERRACOTTA, PORPHYRY, CLASS B ENGINEERING BRICK 75N/MM², LIGHT REINFORCED CONCRETE, BASALT, HARD LIMESTONE, LIMESTONE AGGREGATE CONCRETE, LIGHTLY REINFORCED CONCRETE, CONCRETE PAVERS - CURBS - SLABS, CONCRETE ROOF TILES - PIPES, HARD FACING BRICK, MEDIUM FACING BRICK.

★★★

DUCTILE IRON, DUCTILE IRON, QUARTZITE, REFRACTORY BRICK, SOFT FACING BRICKS, CONCRETE BLOCKS OVER 15N/MM², HARD SLATE, SOFT SLATE, MARBLE, CONCRETE SCREED.

★★



SOFT SANDSTONE (COARSE GRIT), PLASTER - GROUT, CONCRETE BLOCK UNDER 15N/MM², THERMAL BLOCK 7 N/MM².

2X
LASER
WELDED

DRY CUTTING



WET CUTTING



PRODUCT		DIAMETER		SEGMENT HEIGHT		SEGMENT WIDTH		MAIN ARBOR - BORE		REDUCING RINGS INCLUDED		MACHINES USED
PART NO	CODE NO	MM	INCH	MM	INCH	MM	INCH	MM	INCH	MM	INCH	
DA34003	SC10115	115	4 1/2	12	0.472	2.2	0.087	22.23	7/8	N/A	N/A	
DA34004	SC10125	125	5	12	0.472	2.4	0.094	22.23	7/8	N/A	N/A	
DA34005	SC10180	180	7	12	0.472	2.4	0.094	22.23	7/8	N/A	N/A	
DA34006	SC10230	230	9	15	0.590	3	0.118	22.23	7/8	N/A	N/A	
DA34007	SC10300	300	12	15	0.590	3	0.118	25.4 + P	1 + P	25.4 - 20	1 - 20mm	
DA34008	SC10350	350	14	15	0.590	3.2	0.126	25.4 + P	1 + P	25.4 - 20	1 - 20mm	
DA34009	SC10400	410	16	15	0.590	3.4	0.134	25.4 + P	1 + P	25.4 - 20	1 - 20mm	
DA34010	SC10450	450	18	15	0.590	3.6	0.142	25.4 + P	1 + P	N/A	N/A	



WARNING: This product can expose you to "Nickel" which is known to the State of California to cause cancer & birth defects.

ADVERTENCIA: Este producto puede exponerlo a un "Níquel" que el Estado de California sabe que causa cáncer y defectos de nacimiento.

AVERTISSEMENT: ce produit peut vous exposer à un "Nickel" connu de l'État de Californie pour provoquer le cancer et des malformations congénitales. www.P65Warnings.ca.gov



©2023 Caterpillar. All Rights Reserved. CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow", the "Power Edge" & Cat "Modern Hex" trade dress as well as corporate & product identity used herein, are trademarks of Caterpillar & may not be used without permission. C6 DIAMOND LLC, a licensee of Caterpillar Inc.

SILICA DUST: Workers who are exposed to respirable crystalline silica dust are at increased risk of developing serious silica-related diseases. It is necessary to use saws & other machinery that is equipped with an integrated water delivery system that continuously feeds water to the blade. Operate & maintain all tools in accordance with manufacturer's instructions to minimize dust emissions & always wear the correct ventilator. For more info visit: www.osha.gov/sites/default/files/publications/OSHA3681.pdf

catdiamondtools.com

EN2023SC10