



MADE IN



THE USA

PRODUCT DATA SHEET

ROOF REPAIR

DESCRIPTION

EZ On Coat™ Roof Repair is a proprietary blend of polymers. This is a water-based product. EZ On Coat™ Roof Repair evaporates leaving a breathing, heat-reducing monolithic coating. It forms a water-repellent surface that may be coated.

RECOMMENDED USES

This product is designed to be applied over seams and may be applied over most roofing materials such as metal seams, BUR, Modified Asphalt Membranes, Single-Plies, butyl tape and polyester.

APPLICATION

The recommended application for Roof Repair is by extruding or brush. Allow to cure thoroughly prior to application of the base coat. DO NOT THIN. Apply at temperatures of 50° F or greater. Complete cure will take up to 48 hours depending upon ambient temperatures and humidity. This information is general. Read product data sheet or call your rep for more detailed instruction for use.

BENEFITS

- Easy To Apply
- Cleans Easily
- Long Shelf Life
- T2S Formulated
- Single Component
- Pumpable

TECHNICAL DATA

TENSILE:	>450 psi ASTM D-2370
ELONGATION:	>300% ASTM D-2370
COLOR:	Off-White
PERMEABILITY:	6.7 Perms ASTM E-1653
SOLIDS BY WEIGHT:	60% +/- 2% ASTM D-1353
SOLIDS BY VOLUME:	55% +/- 2% ASTM D-2697
WEIGHT:	10.7 lbs. per gallon +/- 2%
VISCOSITY:	80,000 cps @ 100° F
ABRASION:	Passed ASTM D-986
HARDNESS:	55 Shore A ASTM D-2240
STORAGE:	1 year unopened at 40° F - 100° F
DRY TIME:	1 hr. at 75° F and a thickness of 16 wet mils
FULL CURE:	48-72 hours depending on humidity, air movement, and temperature
CLEAN-UP:	Soap and water
ADHESION:	Passed ASTM D-3359
PIGMENT:	Titanium
VOC:	<50 grams per liter

CAUTION: High humidity requires a longer time for water-based coatings to form a film that is rain resistant.

- Avoid breathing fumes and prolonged contact with skin. Do not ingest. Keep containers covered when not in use. When using, provide proper ventilation. Dispose of product and container in accordance with local disposal codes.

CONSULT TECHNICAL DEPARTMENT FOR ANSWERS TO ANY QUESTIONS REGARDING USE OF THIS PRODUCT

System warranty available. When sold separate from system there is no warranty given, expressed or implied, through the values or statements made here, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by our in house and independent third party labs in order to obtain approval and/or classification. Acceptance, purchase and selection of these products are the sole responsibility of the buyer, buyer's agent, or the buyer's customer. EZ On Coat® assumes no responsibility for coverage, performance, or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER GUARANTY OR WARRANTY OF ANY KIND IS MADE BY EZ On Coat® OR ITS SUBSIDIARIES, EXPRESSED OR IMPLIED, STATUORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING COSMETIC APPEARANCE, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.