

# STOP & READ

Begin by sweeping and/or vacuuming the floor clean from debris before unrolling the Floor Protector. Wipe up any dirt, oil or chemicals from the floor. In most cases, the product is rolled on a paper core pattern side out. The product may initially have curl marks—this is normal. The warmer the conditions, the quicker the curl marks will straighten out and lay flat.

Most flooring is shipped pattern out to allow the flooring to lay flat quicker. For larger rolls team lifting is recommended.

**For Garage use:** Start the unrolling process at the entrance of your garage; rolling away from the garage. **Be sure to unroll multiple rolls in the same direction.** Lift the end furthest from the garage and pull the flooring back over itself and into the garage. Gently lift the flooring, fluffing, or forcing air underneath the floor to help position it. When positioned, use a wide push broom to push air out from center and work your way outward side-to-side and front-to-back. It will take some time for most curl marks to lay flat. In cool to cold conditions, it may take 72+ hours before all curls have relaxed. Depending on the temperature, product may expand or contract somewhat during this process. It is fine to park your car on the Floor Protector during this time. Allow proper room (approximately an inch) between the mat and walls or other stationary objects – flooring will need room to relax and may expand or contract as temperatures change seasonally.

**Positioning your flooring for smaller rooms:** Start in a clean larger open area so you can unroll the flooring, then reroll the flooring, so the pattern is facing in toward the core. This will enable you to unroll the flooring in your smaller location with the pattern up.

**Installation:** For garage installations, mats must be completely adhered to the subfloor. In exterior and commercial applications, we recommend securing the mat to the floor with an acrylic-based vinyl adhesive. SBR adhesives (rubber-based) will cause the vinyl flooring to contract and should NOT be used. Acrylic-based adhesive is the only adhesive BLT recommends. Be sure to follow all manufacturer instructions.

For temperature-controlled environments, double sided tape can be used along the perimeter of the mat to secure the edges. The tape should be formulated for use with vinyl flooring and the subfloor you are applying it to.

## ***The longer it sets, the better it will look***

### **CLEANING & CARE:**

The flooring surface is easily washed with vinyl floor cleaner and water. Your new flooring can be easily mopped inside or hosed off outside. Brush or sweep with cool water using a broom or sponge squeegee. Mild soaps and other household detergents suitable for vinyl floors are usually effective. Never leave harsh detergents or chemicals on the flooring. Some people prefer to move the flooring outside and hose it off. You can also clean the flooring using a commercial floor scrubber. Certain automotive vinyl products may cause surface to become slippery. Use a non-slip vinyl protector such as a clean-and-shine floor cleaner. The flooring is not a stain-proof product—certain dyes, inks, rubber tires, and chemicals may cause permanent staining. Some non-permanent stains can be removed with spray-on Brake and Tool Cleaner, without damaging the flooring. This can be found in many auto parts stores; however, the use of Brake and Tool Cleaner may cause product discoloration. Always test in an inconspicuous location of the flooring. Never use harsh chemicals such as tar remover or kerosene on this product.

**⚠ WARNING:** This product can expose you to chemicals including Diisononyl Phthalate (DINP) and Di(2-ethylhexyl)phthalate (DEHP), which are known to the State of California to cause cancer, and Di(2-ethylhexyl)phthalate (DEHP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



For questions please contact:  
913.894.0403  
[customerservice@btllc.com](mailto:customerservice@btllc.com)

*Please fill out form, cut along dotted line, place in an envelope, and return to the address above*


## **WARRANTY REGISTRATION CARD**

**Thank you for choosing Better Life Technology.**

Please fill out the Warranty Registration Card on the back completely and return by mail or visit [info.btllc.com/warranty](http://info.btllc.com/warranty) to complete this registration.

If you have any additional questions or concerns you can visit our website for details at [info.btllc.com/warranty](http://info.btllc.com/warranty) or email us at [warranty@btllc.com](mailto:warranty@btllc.com) and we will gladly assist you.

**Better Life Technology**  
9736 Legler Rd, Lenexa, KS 66219  
913.894.0403  
[warranty@btllc.com](mailto:warranty@btllc.com)



SCAN  
TO REGISTER