



TUB & TILE

Acrylic Latex Caulk
plus SILICONE

TC-10

Interior

A vinyl acrylic tub & tile caulk which gives a water-resistant and mildew resistant seal

PRODUCT DESCRIPTION

LIQUID NAILS® Super Caulk™ Tub and Tile, TC-10, is a vinyl acrylic caulk with silicone which gives a water- and mildew-resistant seal. TC-10 is unaffected by temperature extremes. Flexible and durable with excellent adhesion. This product is strong enough to reset tiles. Easy to apply and clean up.

RECOMMENDED FOR

sealing:

- Tubs
- Sinks
- Backsplashes
- Tub surrounds
- Vanities
- Plumbing fixtures
- Showers
- Countertops
- Windows & doors

TC-10 adheres to:

- Ceramic tiles
- Tileboards
- Porcelain
- Wood
- Painted surfaces
- Plastic tiles
- Vinyl
- Aluminum
- Drywall
- Glass
- Tub surrounds
- Metal
- Marble
- Plaster
- Fiberglass

NOT RECOMMENDED FOR

- On top of silicone
- Gaps wider than 1/2"
- Aquariums
- Wet or green lumber
- Applications below water-line

PRODUCT ADVANTAGES

- Water-resistant
- Durable
- Stays flexible
- Excellent adhesion
- Water clean up
- Gives mildew-resistant seal
- Strong enough to reset loose tiles
- Unaffected by temperature extremes
- Easy to apply and clean up



Please research all installation instructions and read entire label and Material Safety Data Sheet for safety, health & environmental information prior to use. See other cautions on last page.



TUB & TILE

Acrylic Latex Caulk
plus SILICONE

SURFACE PREPARATION

Apply in dry weather above 40° F (4°C). Do not caulk when rain is expected. Remove old caulk. Clean and dry surface. Remove any soap film with rubbing alcohol. **Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead.** Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For additional information, contact the USEPA/Lead Information Hotline at 1-800-424-LEAD.

APPLYING THE PRODUCT

Fill deep joints with backer rod to within 1.3 cm (1/2") of surface. Load into caulking gun. Cut nozzle at 45° angle for desired bead size. Apply continuous bead into gap at 45° angle. Smooth over with wet gloved finger or tool until level with surface. Caulk skins over within 10 minutes. Let dry 24 hours before exposing to water. Humidity may extend dry time.

Coverage: Cartridge: 30 lineal ft. with 1/4" bead. Squeeze tube: 17 lineal ft. with 1/4" bead.

Painting Guidelines: Paintable with oil or latex paint. For best results, wait 24 hours, longer under humid conditions.

CLEAN UP

Use water or mineral spirits when wet. For dry material, scrape and then wipe with mineral spirits.

DISPOSAL

Place **empty** containers in normal refuse for disposal. Remove residual product from the container, allow product to dry, and dispose of in conjunction with normal household waste. Contact your sanitation department or household hazardous waste coordinator for information concerning possible re-use of unused caulks and sealants.

EAD-C8

LIMITED WARRANTY

PPG warrants satisfaction with this product when handled and applied according to label instructions. If product is not as warranted, PPG will, at your option, furnish replacement product or refund the purchase price. Please call 1-800-634-0015 for details. This limited warranty excludes labor or the cost of labor and is given as the exclusive warranty and remedy. **No warranty of merchantability, fitness for purpose or other warranty, express or implied, is made. PPG shall not be liable for any special, incidental or consequential damages.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above exclusions/limitations may not apply. This limited warranty gives specific legal rights; you may have other rights that vary by state.

WARNING! CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF SWALLOWED. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN. Contains Crystalline Silica. If sanding is done, wear a dust mask to avoid breathing of dust. Avoid contact with eyes and skin. **FIRST AID:** In case of skin contact, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be necessary. Remove contaminated clothing. For eye contact, flush **immediately** with large amounts of water for at least 15 minutes. **Obtain emergency medical treatment.** If swallowed, **obtain medical treatment immediately.** If inhalation causes physical discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, **get medical help.** For emergency information, customer service, MSDS or additional safety and chronic hazard information, call 1-800-634-0015. **KEEP FROM FREEZING.**

TC-10 TECHNICAL INFORMATION

Base: Vinyl Acrylic

Type: Waterborne

Color: White

Application Temperature: 40–100° F
(4–38° C)

Service Temperature: -20–200° F
(-29–93° C)

Adhesion: Good to most common bath & kitchen surfaces: ceramic tile, porcelain, glass, aluminum

Extrudability: Excellent

Consistency: Paste

Durability: Excellent

Flexibility: Excellent

Volume Shrinkage: 40-45%

Slump: Max 0.15"

Shore "A" Hardness: 60

Joint Movement: 15% maximum

Water Resistance: Good

Exterior Weathering: Good

Aging: Good

Freeze-Thaw Stable: Passes 5 cycles

Bleed: None

Staining: None

Odor: Mild Latex

Tack Free Time: 10 minutes

Drying Time: Sets in 24 hours

Weight Per Gallon: 10.2 pounds (4.6 kg)

Viscosity: 350,000 to 400,000 CPS

Solids: 75%

Flammability: Nonflammable

Flash Point: Greater than 200°F (93°C)

Coverage: Cartridge - 30 lineal ft. (9.14 lineal meters) using 1/4" (.64cm) bead; Squeeze tube - 17 lineal ft. (5.18 lineal meters)

Shelf Life: One year from date of purchase

VOC: < 1.5% by wt.