OKBRAND



Oklahoma Steel & Wire 1042 South 1st Street Madill, Oklahoma 73446 800.654.4164



lowa Steel & Wire 1500 West Van Buren Centerville, Iowa 52544 800.325.5118



SELECT PANELS

OKBRAND Select Panels are engineered with a unique blend of 5-gauge horizontal wire and 4-gauge vertical wire featuring graduated horizontal spacing. Each panel upholds the high standards of quality and craftsmanship with all OKBRAND fencing products. These panels are designed to tackle the most challenging ranching conditions, yet their versatility extends to various applications, making them ideal for both ranching and lawn and garden projects.

Our galvanized-before-welded process is used on all OKBRAND welded products. Before welding, wires are galvanized using the tight wipe system, which produces a smooth uniform finish. This eliminates sharp burrs or icicles preventing undue injury to animals or people. Galvanizing before welding combines safety with dependable strength and lasting durability.

SELECT PANELS							
PRODUCT	PANEL HEIGHT	PANEL LENGTH	LINE WIRES	HORIZONTAL SPACING	APPROX. WEIGHT LBS.	PANELS PER BUNDLE	ZINC COATING
Select Cattle Panel	50"	16'	10	Graduated	32	50	COMMERCIAL
Select Hog Panel	34"	16'	11	Graduated	29	50	COMMERCIAL
Select Combo Panel	50"	16'	13	Graduated	37	50	COMMERCIAL
Select Sheep and Goat Panel	42"	16'	11	Graduated	32	50	COMMERCIAL