



RUTLAND® Products

Creosote Remover

Item 97, 97S, 97G, 98

Features

- Changes creosote into a brushable powder
- Makes fires burn cleaner
- Improves efficiency of the stove or insert
- Reduces danger of chimney fires

Recommended Uses

Use Creosote Remover in any wood burning fireplace or woodstove.

General Description

Rutland Creosote Remover is a solid granular material that is activated by heat. It modifies creosote by changing it from a sticky tar-like material to a loose powdery non-adhering deposit, which can easily be brushed away.

Limitations

Requires heat to activate. The use of Creosote Remover does not eliminate the need for regular professional chimney cleaning.

Product Information

Surface Prep and Application:

This product requires heat to activate the chemicals.

Tubs: Using the 1 oz. scoop provided in the container, apply one scoop of Creosote Remover to a good bed of coals and then add more fuel and burn hot. Or prepare fire in the normal way and spread one scoop over the fuel, then light the fire.

Toss-In: Creosote Remover in the toss-in stick is pre-measured for convenience. Toss the entire tube onto a brisk fire or hot coals just before rebuilding the fire.

Apply twice weekly for the first month, then once a week for the rest of the heating season. If green wood or low BTU wood is used, twice weekly treatments should continue. To obtain the full effect, stir the ashes daily.

Check elbows or restrictions for blockage. Rutland Creosote Remover changes creosote to ash. Some of the ash will fall down and may block elbows in the flue. Check elbows and restrictions often for blockage as creosote begins to loosen.

Catalytic Converter: Bypass the catalytic converter until the flue temperature is approximately 300°F.

For maximum safety: Rutland recommends a professional chimney cleaning, thereafter pursuing a vigorous preventive maintenance program using Rutland Creosote Remover. The use of Creosote Remover does not eliminate the need for regular chimney cleaning.

Product Usage Key:



Indoor



Outdoor



Pellet Stove



Gas Fireplace



Fireplace



Woodstove

Clean Up:

Toss-in containers burn to ash.

Coverage:

Toss-In: One application per stick or canister.

Tubs: Scoop in container is 1 ounce or 2 tablespoons.

Typical Physical Properties	
Consistency: Granular	Flashpoint: N/A
Color Off: white	Storage/Handling: Store in a dry place and away from sources of ignition
Toss-In Containers: Cellulose; a plant based material	

Warranty & Limited Remedy:

This product will be free from defects in material and manufacture for a period of eighteen (18) months from the date of manufacture. Rutland Fire Clay Company makes no other warranties including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose. User is responsible for determining whether the Rutland Fire Clay Company product is fit for a particular purpose and suitable for user's application. If this Rutland Fire Clay Company product is defective within the warranty period stated above, your exclusive remedy and Rutland Fire Clay Company's sole obligation shall be, at Rutland Fire Clay Company's option, to replace the Rutland Fire Clay Company product or refund the purchase price of the Rutland Fire Clay Company product.

Limitation of Liability:

Except where prohibited by law, Rutland Fire Clay Company will not be liable for any loss or damage arising from this Rutland Fire Clay Company product, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory.

Cautions:

Contains trisodium phosphate and manganese acetate. Do not take internally. Avoid contact with eyes, nose and throat, and prolonged contact with skin. In case of eye contact, flush thoroughly with water. If swallowed, give plenty of water and consult a physician immediately.

KEEP OUT OF REACH OF CHILDREN

HARMFUL IF SWALLOWED

IRRITANT TO EYE

Please direct all inquiries regarding performance of this product to:

Rutland Products

1-800-544-1307

sales@rutland.com

7 Crabtree Rd

Jacksonville, IL 62650