





# TRAILER VALET JX7-P




## Quick Start Guide

NOTE: Prior to install, a mount cylinder must be welded to your trailer in a desired mount location. An existing mount can be used or the mount cylinder included with the unit can be installed. If assistance is needed to weld on the cylinder, please consult your trailer dealer or a welding professional.

|   |                                     |
|---|-------------------------------------|
| <p><b>Check that you have all your parts and accessories.</b></p> |                                     |
| <p><b>TVJX7-P UNIT</b></p>  | <p><b>DRILL ATTACHMENT</b></p>      |
|   | <p><b>SAFETY PIN</b></p>            |
|   | <p><b>WELD-ON PIPE COUPLING</b></p> |
| <p><b>HAND CRANK</b></p>  | <p><b>MANUAL</b></p>                |



- 1.** If necessary, install the mounting cylinder to your trailer frame. Ensure that the jack will have adequate space to be able to switch into a stowed position (horizontal) without hindrance. Raise your trailer tongue to give adequate space to install the jack: approximately 30+ vertical inches from the ground.
- 2.** Place the mount cylinder of the jack over the mount cylinder of the trailer frame. Insert the mounting Safety Pin through the connection point.



- 3.** Attach the Hand Crank to the driveshaft located at the top of the unit. Turning the handle clockwise will extend the jack. Counter-clockwise will retract the jack.
- 4.** Pull Clevis Pin out to lower the drop leg as needed for additional extension of the jack.
- 5.** The Drill Adapter can be used with any standard 20 to 24 volt, 1/2 inch chuck, consumer drill. Corded drills and impact drills are not recommended.

### IMPORTANT SAFETY INFORMATION

For information and assistance, please visit our support page at [TrailerValet.com](http://TrailerValet.com) or give us a call at (844) 846-9344. Scan the QR code to the right for detailed safety and usage information.



 **TRAILER VALET**

**MOVE *FORWARD.***