

PRO TOUCH™

DENT REMOVAL KIT

Instructions for Part #0265


Required Supplies:

Isopropyl Alcohol
Microfiber Cloth
Hi-Temp™ Full-Size Glue Gun
Specially Formulated
Dent-Pulling Glue Sticks
(Included)

Read all safety instructions before beginning.

Follow Glue Gun safe handling instructions.
Follow Dent Puller instructions.

Use on factory automobile paint only.
Do not use on repainted panels.
Do not use on cracked or chipped paint.
Keep fingers out of dent puller mechanism.




1. Locate dent and Clean dent with 91% Isopropyl Alcohol & microfiber cloth



CAUTION: MELTED GLUE WILL BURN SKIN. Nozzle temperature is 380 F (190 C). Do not touch melted glue or nozzle. **IMPORTANT:** Read safety instructions included with gun.


2. Ensure panel is around 75°F, heat or cool panel accordingly. Apply glue to the center of appropriately sized tab and apply to the dent.



3. Wait 2 minutes for glue to cool. Slide Mini Lifter over shaft of glued tab and adjust by turning tension knob until there is slight tension.



4. Squeeze Mini lifter handle to pull dent to desired level or tab breaks free. Use 91% Isopropyl Alcohol to clean glue residue.



5. Inspect dent, some dents require multiple pulls. If pull resulted in a slight mound, tap down high spots using the nylon knock down tools.



Adhesive Technologies, Inc.
Hampton, NH 03842-1995, USA
www.adhesivetech.com

Made in China

LIMITED TWO-YEAR WARRANTY

This product is warranted to be free of manufacturer's defects in workmanship and material for two full years beginning from the date of original retail purchase. This warranty does not cover any damage resulting from accident or misuse. If the product becomes defective within the warranty period, we will repair it or elect to replace it free of charge. We will return your product, provided it is delivered, transportation charges pre-paid, to Adhesive Technologies, Inc. at the address below, with proof of purchase.

Repair or replacement as provided under this warranty is the exclusive remedy of the consumer. Adhesive Technologies, Inc. shall not be liable for any incidental or consequential damages for breach of any express or implied warranty on this product. Any implied warranty of merchantability or fitness for a particular purpose on this product is limited in duration to two years from date of purchase.