

Install generator set into silent box



Installation Manual



- 1** Measure the maximum width dimension of your generator set.



- 2** Measure the width of the side panel and the front panel.



- 3** Remove the left or right side panel and move the unit into the enclosure.



- 4** Based on the two measurements you made, determine if you need to remove the posts to make it easier to place your generator inside the enclosure.



- 5** Place your generator into the enclosure, making sure it has proper clearance on all sides.



- 6** Be sure to plug the fan's plug into your generator. Make sure the fan is working when the generator set is running.



7 Install one end of the three springs into the clamp ring. (As shown in the attached picture)



8 Install the rectangular spacer into the bend of the clamp ring.



9 Insert the round flat washer between the clamp ring and the square washer and pre-tighten it with hand.



10 Complete the small component assembly.



11 Connect the silicone tube to the unchamfered end of the 90° metal bellows.



12 Then tighten it with the clamp ring assembly.



13 Install the exhaust bellows to the rear panel of the enclosure.
Bend the metal tube by hand to adjust it to the appropriate angle.



14 Install the 90° metal bellows together with the silicone tube and clamp assembly onto the exhaust bellows.



15 Bend it by hand and adjust the angle and position of the bellows assembly so that it faces the exhaust port of the engine muffler.
Then fix the three spring hooks on the muffler guard.



16 Select expansion screws with appropriate outer diameters, pass them through the holes of the four brackets, and securely mount the chassis to the ground or other locations.



Note : If the color of any actual object does not match the photos in the instructions, the actual object shall prevail.