

URIAH PRODUCTS 15' RV SEWER HOSE KIT

Setup Instructions:

1. Prepare the Hose: Remove the Uriah Products RV sewer hose from storage. Extend the hose to the desired length, ensuring it reaches from your RV's waste outlet to the dump station connection without excessive slack or tension. The hose is designed to hold its shape once extended.
2. Connect to RV Waste Outlet: Attach one end of the Uriah Products RV sewer hose (with the pre-attached swivel bayonet fitting) to your RV's waste outlet. Ensure the connection is secure and the locking tabs are engaged to prevent leaks.
3. Attach Clear Elbow and Adapter: Connect the clear elbow with the 4-in-1 adapter to the other end of the Uriah Products RV sewer hose. The swivel fitting on the elbow allows for easy alignment.
4. Connect to Dump Station: Insert the 4-in-1 adapter into the dump station's sewer inlet. The adapter is designed to fit 3" slip or 3", 3 1/2", and 4" NPT threaded pipes. Ensure a snug and secure fit.
5. Position the Hose: Arrange the hose to ensure a continuous downward slope from your RV to the dump station to facilitate proper drainage. Use a hose support system (not included in this kit) if necessary to maintain the slope and keep the hose off the ground.

Operating Instructions:

1. Wear Protective Gear: Always wear appropriate protective gloves when handling sewer equipment.
2. Open Black Tank Valve First: Once the hose is securely connected to both your RV and the dump station, open the black tank valve first. The clear elbow will allow you to monitor the flow and see when the tank is empty.
3. Flush Black Tank (Optional but Recommended): After the black tank is empty, close its valve. If your RV has a black tank flush system, connect a separate hose (not your potable water hose) to the flush inlet and run water until the clear elbow shows clear water flowing.
4. Open Gray Tank Valve: Close the black tank valve (if flushed). Then, open the gray tank valve. The gray water will help rinse the sewer hose. Monitor the flow through the clear elbow until the gray tank is empty.
5. Close Valves: Close the gray tank valve.

Storage:

1. **Disconnect and Cap:** After rinsing, disconnect the hose from both the RV and the dump station. Attach the provided RV sewer caps to both ends of the hose to prevent drips and odors during storage.
2. **Compress the Hose:** The Uriah Products RV sewer hose is designed to compress for compact storage. Push the hose together to reduce its length to approximately 56 inches.
3. **Store in Bumper:** If desired, remove the 4-in-1 adapter from the clear elbow. The compressed hose (without the 4-in-1 adapter) can then be neatly stored inside a standard 4" square RV bumper.

Troubleshooting:

Problem	Possible Cause	Solution
Leaks at connections	Loose connection, damaged gasket, improper alignment.	Ensure fittings are securely locked. Inspect and replace damaged gaskets. Realign connections.
Slow drainage	Insufficient slope, partial clog in hose or tank.	Adjust hose support to ensure proper downward slope. Check for clogs in the hose or RV tanks.
Hose does not compress fully	Debris inside hose, internal damage.	Ensure hose is clean and free of debris. Inspect for internal damage that might prevent compression.