# DRAFT & INSULATION TAPE

## TECHNICAL DATA SHEET

### DESCRIPTION

Flex Seal® Draft & Insulation Tape is a flexible, rubberized, weatherproof strip that instantly seals gaps around windows, doors, vents, and more. It keeps out air, dust, and moisture and blocks cold winter drafts and hot summer air. It reduces energy costs, improving year-round comfort. Once Flex Seal Draft & Insulation Tape is applied, doors and windows will continue to open and close normally. It's easily removable and can be repositioned. And its clear design blends in seamlessly. Best of all, it can be applied in seconds – no mess. Just cut, peel, and stick.

### FEATURES

- **2" wide coverage –** even seals large gaps.
- **Strong adhesion –** stays put through rain, wind and extreme temperatures.
- **Weather & moisture resistant –** use indoors or outdoors, even in extreme weather.
- **Clear protection –** transparent design blends in anywhere.
- **Flexible rubberized strip –** maintains shape, seals tight without cracking.
- **Repositionable –** easy to adjust and reuse.
- **No tools needed –** Just cut, peel & stick.
- **Year-round comfort –** blocks out air & moisture.
- **Save money on energy –** helps lower heating & cooling costs.

### TECHNICAL SPECIFICATIONS

- **Material –** rubberized backing.
- **Adhesive –** pressure-sensitive adhesive.
- **Application temperature –** 41°F (5°C) to 113°F (45°C).

### COMMON APPLICATIONS

Windows, doors, vents, attic hatches, shower doors.

### COMMON BONDING SUBSTRATES

Smooth, non-porous surfaces: painted wood, glass, tile, metal, plastic, fiberglass.

### STORAGE

- Store unused tape in a sealed plastic bag between uses.
- Store in a cool and dry place between 41°F (5°C) and 81°F (27°C), with humidity between 30% and 70%.

### SIZE AND COLOR

- 2 in x 16 ft roll, clear.

### USAGE INSTRUCTIONS

**1.** Clean & dry the surface. For glass or metal, use cleaner for best results.

**2.** Measure & cut one strip at a time to your desired length.

**3.** Peel off backing to expose adhesive.

**4.** Apply with adhesive side down and the non-adhesive flap covering the gap.

**5.** Press firmly for 15-30 seconds to ensure a secure bond.

**6.** To remove, peel slowly. Rinse tape with water to reuse. Let air dry completely.

### USAGE GUIDELINES

1. Test on a sample surface to confirm the tape is suitable before use.
2. Avoid using on painted walls, wallpaper, or drywall.
3. Avoid use on wet, oily, uneven, or nonstick surfaces.
4. Removal from delicate surfaces may cause damage or leave residue.
5. Improper installation may cause damage to surfaces.

### SAFETY INFORMATION

- Keep the product out of reach of children.
- Before application, please carefully read the product instructions.

### CONTACT INFORMATION

For technical assistance or additional information, visit www.flexsealproducts.com or contact customer support.